文件:	名称 System Name:	产品品名 Desc	ription:	文件组	扁号 Docu	ment N	lo.:
					PS-008	33	
Pro	duct specification	1.3Pitch 0.9H FTB C	ONNECTOR	Page	1 OF 9	Rev.	>
-		***** 目 錄 Con 內 容 Descrij 	otion	****		Page	
	核准 <b>App</b> .	审核 Chk.	制作 Pre	<u>.</u>	Issue	ed By:	
			王帅				
y	郑大春	王团伟	ደ እስ			帅	

## \*\*\*\*\*\* Copyright is reserved by FAF \*\*\*\*\*\*

FAF.



文件名称 System Name:	产品品名 Description:	文件编号 Document No.:			lo.:
Product specification		PS-0083			
	1.3Pitch 0.9H FTB CONNECTOR	Page	2 OF 9	Rev.	X1

Edition	ECN NO.	Revised Page	Remark
X1		Initial Release	

# Kunshan Jiahua Electronics Co., Ltd.

文件名称 System Name:	产品品名 Description:	文件编号 Document No.:			lo.:
Product specification		PS-008		33	
	1.3Pitch 0.9H FTB CONNECTOR	Page	3 OF 9	Rev.	X1

#### 1. 概述 Scope:

#### 1.1 说明 Content

此份产品规格书是针对由昆山嘉华电子有限公司设计和制造的 1.3Pitch 0.9H FTB CONNECTOR 产品所定义的产品性能和测试方法。

This product specification defines the product performance and the test methods to ensure the performance of the **1.3Pitch 0.9H FTB CONNECTOR**, which is designed and manufactured by Kunshan Jiahua Electronics Co., Ltd.

#### 1.2 限制 Qualification

所有的测试和检验必须依照本文件中所要求的规格、方法进行。一旦产品的重要制程发生 变更,必须立即进行品质验证和测试。

Tests and inspection shall be performed in accordance with the requirements, tests and methods contained herein. A re-qualification test shall be conducted immediately following all major process changes.

#### 2. 参考文件 Referenced Documents:

EIA-364 MIL-STD-202F MIL-P-81728A MIL-T-10727B JIS C 0040 JIS C 0041

若某些项目被发现本规格书中的内容与以上参考文件要求不一致时,一律依本规格书中的内容为测试依据。

In case of any contradiction between this document and referenced documents, this document will take precedence.

\*\*\*\*\*\* Copyright is reserved by FAF \*\*\*\*\*\*

保存期限:该产品停产后1日历年

# **Kunshan Jiahua Electronics Co., Ltd.**

文件名称 System Name:	产品品名 Description:	文件编号 Document No.:			lo.:
Product specification		PS-0083			
	1.3Pitch 0.9H FTB CONNECTOR	Page	4 OF 9	Rev.	X1

## 3. 规格要求 Requirements:

3.1 应用条件 Application Condition:

3.1.1 额定电流: 3.0Amps per contact CURRENT RATING: 3.0Amps per contact
3.1.2 额定电压: 30 Volt DC/AC. VOLTAGE RATING: 30 Volt DC/ AC

3.1.3 使用环境 Operating Environment:

温度: -25°C to +85°C。

Temperature:-25°C to +85°C.

3.1.4 储存环境 Storage Environment:

温度: -40°C to +85°C,相对湿度:15%~70%或更低,此条件下功能不可失效。

Temperature:-40°C to +85°C, Relative Humidity: 15%~70% or Less, Without loss of function.

3.2 绿色环保要求 Health, Safety and Environment

此产品中所有涉及环保有关的有害物质管控标准请参考嘉华系统文件:JH-GP-213

Hazardous substances (Environment related to be controlled substances) contained in this product should comply with the regulations specified by FAF's <u>JH-GP-213</u>.

### 3.3 测试说明 Test Description

此产品性能须满足本文件第4节中的各项规格要求。除非有特别申明,所有的测试和量测必须在以下条件中进行:

The product is designed to meet the requirements specified in section 3.4. Unless otherwise specified, all tests and measurements are to be performed under the following conditions:

温度 Temperature: 5 ℃to 35℃

相对湿度 Relative Humidity: 45% to 85%

大气压 Atmospheric Pressure: 86kPa~106kPa.

### \*\*\*\*\*\* Copyright is reserved by FAF \*\*\*\*\*\*

保存期限:该产品停产后1日历年

# FAF. Kunshan Jiahua Electronics Co., Ltd.

文件名称 System Name:	产品品名 Description:	文件组	文件编号 Document No.: PS-0083		
Product specification				3	
	1.3Pitch 0.9H FTB CONNECTOR	Page	5 OF 9	Rev.	X1

4.1 外观 Appearance		
项目	规格要求 Requirements	测试方法 Test Methods
4.1 产品外观和尺寸检查	所有零件必须组装完好,不能出现毛边,变 形,刮伤,以及任何外观破坏等异常;	依照相应的又件和规格书进行外观,切能, 及尺寸的检验量测.
Appearance	All components shall be properly assembled and free of burrs, warps, scratches, broken chips, and other abnormalities	Visual, functional, and dimensional inspection complies with applicable specification and document.
4.2 电气 性能 Electric	al Performance :	
<b>4.2.1</b> 接触阻抗	初始接触阻抗: 20mΩMax; 试验后接触阻抗: 40mΩMax;	测量接触阻抗,测试电流小于 10mA Measure contact resistance of product and test card PCB with less than current
Low level contact resistance	Initial: 20m $\Omega$ Max;	of 10 mA ( exception for the conductor resistance)
	After test: 40m $\Omega$ Max;	
4.2.2 绝缘阻抗 Insulation resistance	初始绝缘阻抗: 1000 M Ω Mn 试验后绝缘阻抗: 1000 M Ω Mn Initial:1000 M Ω Mn	测试电压:直流 200V ,测试时间:2分钟,测试相邻两端子之间的绝缘阻抗 Give DC 200V Voltage for 2 minutes and then measure insulation resistance of
	After test:1000 M Ω Min	contact and contact
4.2.3 耐电压 Dielectric withstanding voltage	产品既无电火花也无气体产生 漏电流最大 2mA After the test, Neither creeping discharge nor flashover shall occur. Leakage current 2 mA Max	两相邻端子之间加载交流 500V 电压 1 分 钟;温度冲击和恒温恒湿后为交流 300V Give AC 500 V in near contact and insulator for 1 minute After tests:300V AC(Thermal shock& Humidity)
4.2.4 温度上升 Temperature rise	<ul> <li>额定电流状态下,使用热电偶方式测量,只串联电源 Pin</li> <li>The power source terminal shall be connected in a direct series. The temperature rise shall be measured by thermocouple when the temperature of terminal reaches to rated current with resistive load.</li> </ul>	温度上升 30K Max. Temperature rise:30K Max.

#### |4.3 机械 性能 Mechanical Performance:

# F/F. Kunshan Jiahua Electronics Co., Ltd.

文件名称 System Name:	产品品名 Description:	文件编号 Document No.:			lo.:
Product specification			PS-008	083	
	1.3Pitch 0.9H FTB CONNECTOR	Page	6 OF 9	Rev.	X1

4.3.1 插拔力 Insertion force& Withdrawal force	1.Plug 端插入力::40N Max. 2. Plug 端拔出力: 3NMin . 1. Plug Mating force:40N Max 2. Plug withdrawal force: 3N Min	产品焊板后,测量 Plug 端的插拔力,测试 速度: 1~5mm/sec 测试时 plug 端须以插入轴向上下插拔 After Soldering of testing product at PCB, Measure insertion and withdrawal force of Plug at 1~5mm/sec to mating axis
4.3.2 耐久 Durability	<ol> <li>试验后接触阻抗: 40mΩMax;</li> <li>产品无断裂、无破损;</li> <li>拔出力: 3N Min;</li> <li>Aftertesting,contact resistance : 20mΩMax;</li> <li>No have fracture, crack, terminal contact point deflection and shake of product</li> </ol>	产品焊板后,重复插拔 Plug 端,耐久 10 次; After Soldering of testing product at PCB, Repeat insert/ withdrawal of plug as 10 cycle;
4.3.3 振动 Vibration	3.Withdrawal force:3N Min; 1. 试验后接触阻抗: 20m Ω Max; 2.没有物理损坏,端子无变形 3. 不产生超过 1 微秒的瞬断 1.After testing, contact resistance : <b>20mΩ Mx;</b> 2.No have fracture, crack, terminal contact point shake of product 3. No electrical discontinuity longer than 1 u sec.	产品焊板后测试, 测试频率: 10-55-10HZ, 振幅: 1.52mm,X,Y,Z 三个方向每个方向 振动两个小时, (sweep time:30s) After attach at vibration plate and Soldering at test PCB, it test follow conditions : As condition of frequency:10-55- 10HZ,amplitude1.52mm,it test for two hours about each of X,Y,Z, axis(sweep time:30s)
4.3.4 物理冲击 Physical shock	不产生超过 0.1 微秒的瞬断,产品没有物 理破坏以及零件脱落,端子接触阻抗满足 规格要求.	参考测试标准: EIA-364-27. 波形:半正弦波; 加速度: 50G, 沿 X,Y,X 三个方向进行, 每个方向完成正反 各 3 次冲击(总计 18 次冲击)
	No electrical discontinuity longer than 0.1 microsecond. No mechanical damage or looseness.Contact resistance specifications remain satisfied.	Comply with method EIA-364-27B, Shock Waveform: Half sine-wave, Acceleration: 50G, Total impacts delivered 3. each along X. Y. and Z axes.(Total:18 impacts)
4.3.5 端子保持力 Contact retention force	至少 0.5N; 0.5N Min;	端子在塑胶退出时的保持力. 退出速度为 25±3mm/min. Measured withdrawal force that resin grips and supports terminal. Velocity of withdrawal:25±3mm/min.

# FAF. Kunshan Jiahua Electronics Co., Ltd.

文件名称 System Name:	产品品名 Description:	文件编号 Document No.:			lo.:
Product specification		PS-0083			
	1.3Pitch 0.9H FTB CONNECTOR	Page	7 OF 9	Rev.	X1

项目 Items	规格要求 Requirements	测试方法 Test Methods
4.4 环境 性能 Environm	ental Performance :	· ·
4.4.1 耐高温 High temperature	<ol> <li>产品无损坏,端子无变形</li> <li>2.试验后接触阻抗: 40mΩ Mx;</li> <li>1.No have fracture crack ,terminal contact point deflection and shake of product</li> <li>2.After testing contact resistance:</li> <li>20mΩ Mx;</li> </ol>	配合后的产品在以下条件下测试: 温度: 85±2°C 时间: 96h Mated connectors shall be subjected to the following condition: temperature: 85±2°C Duration: 96h
4.4.2 耐低温 Low temperature	1 产品无损坏,端子无变形 2.试验后接触阻抗: <b>40mΩ Mx;</b>	配合后的产品在以下条件下测试: 温度: -40±3℃ 时间: 96h
	1.No have fracture crack ,terminal contact point deflection and shake of product 2.After testing contact resistance: <b>40m</b> Ω <b>Mx;</b>	Mated connectors shall be subjected to the following condition: temperature: -40±3°C Duration: 96h
4.4.3 耐硫化性 Resistance to sulfuration	<ol> <li>试验后接触阻抗: 40mΩ Max;</li> <li>无外观异常</li> <li>1.After testing contact resistance:</li> <li>40mΩ Max;</li> <li>2.Without distinct damage i appearance</li> </ol>	配合后的产品在以下条件下测试: 浓度: 10±3ppm 温度: 40±2°C 相对湿度: 70±5% 时间: 96h Mated connectors shall be subjected to the following condition: Concentration: 10±3ppm Temperature: 40±2°C Relative humidity: 70±5% Period: 96 hours
4.4.4 热冲击 Thermal shock	测试后满足相应机械及电气规格; 测试后接触阻抗: 40mî Max;	参考测试标准: EIA-364-32; -55℃和+85℃各 30 分钟,总计 25 个 循环.
	After test: <b>40mΩ Mrx;</b>	Comply with method EIA-364-32. -55°C for 30 minutes and +85°C for 30 minutes for 25 cycles.

# F/F. Kunshan Jiahua Electronics Co., Ltd.

文件名称 System Name:	产品品名 Description:	文件编号 Document No.:			lo.:
		PS-0083			
Product specification	1.3Pitch 0.9H FTB CONNECTOR	Page	8 OF 9	Rev.	X1

4.4.5 恒温恒湿 Humidity	<ol> <li>产品无损坏,端子无变形</li> <li>试验后接触阻抗: 40mΩMx;</li> <li>试验后绝缘阻抗: 1000MΩMin.</li> <li>试验后耐电压: 无损坏</li> <li>No have fracture crack ,terminal contact point deflection and shake of product</li> <li>After testing contact resistance:</li> <li>40mΩMx;</li> <li>After testing insulation resistance: more than 1000 MΩ</li> <li>After testing Dielectric withstanding voltage: Without damage</li> </ol>	配合后的产品在以下条件下测试: 温度: 60±3°C; 相对湿度: 90~95% 时间: 96 hours Mated connectors shall be subjected to the following condition: Temperature: 60±3°C Relative humidity: 90 to 95% Period: 96 hours
4.4.6 盐雾测试 Salt Spray Test	<ul> <li>1.产品无损坏,端子无变形</li> <li>2.试验后接触阻抗: 40mΩ Max;</li> <li>1. No have fracture crack ,terminal contact point deflection and shake of product</li> <li>2. After testing contact resistance: 40mΩMax;</li> </ul>	盐水浓度: 5±1% 时间: 48 小时 温度: 35±2°C Mated connector shall be subjected to the following condition Concentration : 5±1% Spray time : 48hours
4.4.7 耐 Reflow 高温 Resistance to Reflow Soldering Heat	<ul> <li>1.无损坏,端子无变形;</li> <li>2.产品结构无破坏;</li> <li>1.No have fracture crack ,terminal contact point deflection and shake of product</li> <li>2.No have break down outer feature/structure</li> </ul>	Temperature : $35\pm 2^{\circ}$ C 根据下图温度条件测试产品的耐焊接 热 The connector shall be tested resistance to soldering heat in the following conditions, The temperature shall be measured on the surface of PCB 260°C
4.4.8 吃锡性测试 Solder ability	焊脚吃锡面积 95%以上 More than 95% of area dipped in molten solder should be coated by solder	温度: 245℃±5℃ 粘锡时间: 3±0.5 秒 Solder Temperature : 245℃±5℃ Immersion Duration : 3±0.5 seconds

\*\*\*\*\*\* Copyright is reserved by FAF \*\*\*\*\*\*

保存期限:该产品停产后**1**日历年 文件编号:**QP-07-04/09A** 

# **F**/**F**<sub>0</sub> Kunshan Jiahua Electronics Co., Ltd.

文件名称 System Name:	产品品名 Description:	文件编号 Document No.:					
Product specification		PS-0083					
	1.3Pitch 0.9H FTB CONNECTOR	Page	9 OF 9	Rev.	X1		

Test, Measurement or Examination	А	В	С	D	Е	F	G	н	I	J	к	L
	Sample size	Samp size										
	5	5	5	5	5	5	5	5	5	5	5	5
1. Visual examination 产品外观	1 ,9	1,9	1 ,6	1,3	1	1,7	1,7	1,5	1,5	1,7	1,3	1,3
2. Low Level Contact Resistance 低功率接触阻抗	2,6	2,8	2,5			2,5	2,5	2,4	2,4	2,5		
3. Insulation Resistance 绝缘阻抗	3,7					3,6	3,6			3,6		
4. Dielectric Withstanding Voltage 耐电压	4,8											
5. Temperature rise 温度上升				2								
6. Mating and Unmating Force 插拔力		3, 6 4, 7										
7. Durability 耐久插拔		5										
8. Vibration 振动			3									
9. Mechanical Shock 机械冲击			4									
10. Terminal retention forces 端子保持力					2							
11. Cold Resistance 低温测试						4						
12. Temperature life 温度寿命							4					
13. Resistance to sulfuration 耐硫化性								3				
14. Thermal shock 温度冲击									3			
15. Humidity 耐湿性能	5											
16. Salt Spray 盐雾实验										4		
17.Resistance to Reflow Soldering Heat Reflow 耐高温											2	
18. Solder-ability 可焊性												2